

PART # 24DP-XHD  
BCI 24M  
VOLTAGE 12V  
Ah 65



### PHYSICAL SPECIFICATIONS

| Battery Type | Weight               | Dimensions (L x W x H)                           | Container Material | Cover Material | Separator Material | Handle Option |
|--------------|----------------------|--|--------------------|----------------|--------------------|---------------|
| Flooded      | 40.8 lbs<br>18.5 kgs | 10.188 x 6.77 x 8.648"<br>258.8 x 172 x 219.7 mm | Polypropylene      | Polypropylene  | Polyethylene       | Yes           |

### ELECTRICAL SPECIFICATIONS

| Nominal Voltage | SAE CCA (-18°C/0°F) | SAE CA (0°C/32°F) | SAE RC (27°C/80°F) | Ref. Ah Capacity 20 Hr | Battery Terminal Type  | Electrolyte Specific Gravity Range |
|-----------------|---------------------|-------------------|--------------------|------------------------|------------------------|------------------------------------|
| 12.6 V          | 560 A               | 700 A             | 120 Min            | 65 Ah                  | Threaded Marine Type M | 1.270-1.300                        |

### MISC SPECIFICATIONS

|                           |                  |
|---------------------------|------------------|
| Maximum Discharge Current | 1000 A (5 sec)   |
| Positive Grid Alloy       | Lead Calcium Tin |
| Negative Grid Alloy       | Lead Calcium     |
| Terminal Polarity         | + -              |

